



delair (india) pvt. ltd.

21C, Sector 18, Gurgaon-122015

Phone : 91-124-4091111 Fax : 91-124-4091100

E-Mail: delair@pahwa.com

TECHNICAL SPECIFICATION

BULLETIN NO. : DAI:MS-600.1
 EFFECTIVE : JAN 02, 2006
 SUPERSEDS : DAI:MS-600.0
 DATED : SEPT 30, 2002

MOISTURE SEPARATOR

MOISTURE SEPARATOR STANDARD WITH

SPECIAL FEATURES

- WIDE RANGE OF 15 STANDARD MODELS WITH CAPACITIES FROM 50 M3/HR. TO 6000 M3/HR.
- HIGHER CAPACITIES - AVAILABLE ON REQUEST
- COMPACT DESIGN
- MOISTURE SEPERATOR IN ACCORDANCE WITH INTERNATIONAL DESIGN CODE LIKE- ASME , IS-2825 , BS ETC.
- INSTRUMENTATION SUCH AS – MANUAL DRAIN VALVE ETC. MOISTURE SEPERATOR
- DULY TESTED – PNEUMATICALLY & HYDROSTATICALLY

OPTIONAL FEATURES

- AUTO DRAIN VALVE
- CONSTRUCTION ACCORDANCE TO OTHER VARIOUS CODES
- DEMISTER PAD TYPE

MODEL NO.	CAPACITY IN M3/HR	DIMENSIONS (IN MM)		CONNECTION (IN MM)
		D	H	
MS-50	50	150	950	N1 & N2 20
MS-100	100	150	950	20
MS-250	250	200	1050	40
MS-500	500	200	1050	50
MS-750	750	250	1100	65
MS-1000	1000	300	1100	80
MS-1250	1250	300	1100	80
MS-1500	1500	350	1300	100
MS-1750	1750	350	1300	100
MS-2000	2000	450	1300	100
MS-2500	2500	450	1300	100
MS-3000	3000	500	1500	150
MS-3500	3500	500	1500	150
MS-4500	4500	600	1500	150
MS-6000	6000	600	1500	150

