


**AIR RECEIVER
WITHOUT HOLE**

AIR RECEIVER STANDARD WITH

SPECIAL FEATURES	OPTIONAL FEATURES	STD. WORKING PARAMETERS
<ul style="list-style-type: none"> Wide range of 11 standard models Capacities from 0.5 m3 to 15.0 m3. Higher capacities - available on request Compact design Receivers in accordance with delair standard design code. Instrumentation such as – pressure gauge, safety relief valve, manual drain etc. with receiver. Duly tested – pneumatically & hydrostatically 	<ul style="list-style-type: none"> Auto drain valve Construction according to other various codes 	<ul style="list-style-type: none"> Pressure :- 7.0 Kg/Cm2(g) Temperature :- Upto 60 Deg. C * Note :- For other working conditions please contact factory

Specification Sheet for Air Receiver Without Hole

MODEL NO.	CAPACITY IN M3	DIMENSIONS (IN MM)		CONNECTION (IN MM)	WEIGHT (IN KG)
		D	H		
REC-0.5	0.5	700	1915	50	215
REC-1.0	1.0	850	2385	50	365
REC-1.5	1.5	1050	2440	50	475
REC-2.0	2.0	1150	2570	50	535
REC-3.0	3.0	1150	3590	65	710
REC-4.0	4.0	1300	3635	65	815
REC-5.0	5.0	1350	4180	65	960
REC-6.0	6.0	1500	4135	80	1370
REC-7.5	7.5	1600	4275	100	1520
REC-10.0	10.0	1850	4420	100	2250
REC-15.0	15.0	2250	4530	150	3375



ALL DATA SUBJECT TO CHANGE WITHOUT NOTICE